

Technical Datasheet

Product Code: **A3092C**

Product Description: **Dual Thermostatic Shower Valve**

Specification

| | |
|----------------------------|-------------------|
| Product Guarantee: | 5 Years |
| Barcode: | 5055275832936 |
| Material: | Brass |
| Handle Type: | Crosshead & Lever |
| Min Operating Pressure: | 0.1 Bar |
| Flow Rate 0.1 Bar (L/min): | 5.5 |
| Flow Rate 0.5 Bar (L/min): | 14.5 |
| Flow Rate 1 Bar (L/min): | 22 |
| Flow Rate 2 Bar (L/min): | 30 |
| Flow Rate 3 Bar (L/min): | 35 |
| Colour: | Chrome |



Key Features

- Bring a Victorian sensibility to your bathroom with this traditional shower
- Accurate flow control
- Thermostatic control to +/- 2 to 3 °C even if the water pressure fluctuates
- In the event of hot or cold water failure, the valve will shut down the water supply providing full
- The unique cartridge is highly resistant to calcium build up - even in hard water areas
- Our valves are suitable for use with all systems: gravity fed pumped unvented high pressure or fully
- Excellent flow rates - even at low pressure
- The cartridge is fully reversible meaning if hot and cold supplies are the wrong way round it doesn't
- Simply remove the cartridge turn 180° and replace
- Manufactured from solid brass

Dimensions: All measurements are in millimetres and are subject to normal manufacturing variations.

Due to a continuing development programme to improve design and performance, we reserve all rights to vary specifications without prior notice. Please note, all accessories are for photographic purposes only.

Technical Datasheet

Product Code: **A3092C**

Product Description: **Dual Thermostatic Shower Valve**

Technical Drawing

